

KASHI FR 8275-01

Technical protective gloves against mechanical and thermal risks. This model has added protection on the back of the user's hand, thanks to the placement of a protective lining in this area. The gloves are hydrophobic, oleophobic, and the user's comfort is ensured by a sophisticated anatomical cut with overstretched seams on the fingertips.



KASHI FR

Colour: Neon Yellow 
KASHI FR 8275-01

UPPER MATERIAL:

- Back: Resistant textile with reduced flammability with hydrophobic and oleophobic treatment.
- Palm and interstitial: Elastic Para-Aramid / Polyamide knit with silicone coating.

REINFORCEMENT:

- Protection of the knuckles on the back of the hand against abrasion and impact – Kevlar® / Polyamide with FR coating backed with foam.
- The reinforcement between the thumb and index finger made of Kevlar® fabric with FR coating overlaps the side seams, thanks to the high resistance to abrasion increases the durability of the glove.

LINING:

- Palm and back: Para-aramid / Polyester / fiberglass knit lining - high cut resistance.
- Cuff: Non-flammable inner FR knitted material preventing the penetration of dirt into the glove.

CUT RESISTANT INTERMEDIATE LAYER:

- Palm: 100% aramid non-woven fabric.

CUFF:

- **Evo:** Elastic cuff finished with a rubber band against dirt.



STANDARDS:

- EN 388:2016+A1:2018
- EN 407:2020
- EN ISO 21420:2021

KASHI FR 8275-01

OTHER INFORMATION:

- Anatomic cut, breathability, sensitivity, flexibility.
- All-over non-flammable glove.
- Highly hydrophobic and oleophobic.
- High resistance to mechanical risks in palm and on the back.
- Above average mechanical resistance in the interfingers.
- Excellent grip and sensitivity thanks to the special design of the extended fingertips.
- High-vis, reflective element on back of glove.
- Comfortable – flexible – anatomically shaped cut including the thumb.
- The wrist part is tightened with elastic band.
- Non-flammable loop on the cuff for easier putting on the glove and for hanging on a carabiner.
- The gloves can be washed at 60 °C.



Reinforcement made of Kevlar® with FR coating



Cut-resistant elastic knitted palm

SIZE ASSORTMENT:

 cm	15,2-16,5	16,5 - 19	19 - 21,6	21,6 - 24,2	24,2 - 26,7	26,7 - 29,2	29,2 - 30,4
size	6 (XS)	7 (S)	8 (M)	9 (L)	10 (XL)	11 (2XL)	12 (3XL)

CARE & MAINTENANCE:

Choose a more ecological short washing program at 40 °C. Wash at a maximum temperature of 60 °C if you need to disinfect the gloves or they are extremely dirty.



PROCEDURE: Remove coarse dirt after each use. Before washing, fasten the Velcro fasteners and remove the snaps. Use a liquid detergent. Wash on a short programme.

TO MAKE THE GLOVE FIT BETTER: Shape the glove several times after washing and during drying. Do not dry in direct sunlight or heat sources, do not use a tumble dryer. Store the gloves in a dry environment.

For more about Washing & Maintenance, visit:
www.holik.com > Technologies > Care&Maintenance

Measurement type:	Results:
Abrasion resistance	3
Blade cut resistance (palm part)	4 / TDM Level D
Tear resistance	4
Puncture resistance	3
Burning behaviour	4
Convection heat resistance	2
Radiant heat resistance	2
Contact heat resistance	1
Dexterity	5



Co-funded by
the European Union

